

## TUERCA - INSERTO REMACHABLE

Tamaño	Capacidad de Agarre		Perforacion	A (Ref)	D (-0.1 - +0.07)	DK	K	L
	Minimo	Maximo						
M3	0.50	1.50	5.00	6.00	4.90	7.50	0.80	9.00
M4	0.50	2.00	6.00	6.00	5.90	9.00	0.80	11.00
	2.00	3.50						12.50
M5	0.50	2.50	7.00	7.50	6.90	10.00	1.00	13.00
	2.50	5.00		8.50				15.50
M6	0.50	3.00	9.00	9.20	8.90	12.3(13.0)	1.30	15.00
	3.00	5.50		10.50				19.00
M8	1.00	3.50	11.00	11.50	10.90	14.5(16.0)	1.50	18.00
	3.50	6.00						20.50
M10	1.00	4.00	13.00	13.50	12.90	17.0(19.0)	1.70	21.00
	4.00	6.50						23.50
	1.00	3.50						12.00
M12	1.00	4.00	15.00	13.50	14.90	18.00	1.70	22.00
	4.00	6.50		14.00				25.00
	1.00	3.50	16.00	15.00	15.90	22.00	2.00	25.00
	1.00	3.50		16.00				28.00

Tamaño	Capacidad de Agarre		Perforacion	A (Ref)	D (-0.1 - +0.07)	DK	K	L
	Minimo	Maximo						
10-24 UNC	0.50	2.50	7.00	7.50	6.90	10.00	1.00	13.00
10-24 UNC	2.50	5.00	7.00	8.50	6.90	10.00	1.00	16.50
10-32 UNF	0.50	2.50	7.00	7.50	6.90	10.00	1.00	13.00
10-24 UNF	2.50	5.00	7.00	8.50	6.90	10.00	1.00	16.50
1/4-20 UNC	0.50	3.00	9.00	9.20	8.90	12.30	1.30	15.00
1/4-20 UNC	3.00	6.00	9.00	10.50	8.90	12.30	1.30	19.00
5/16-18 UNC	1.00	3.50	11.00	11.50	10.90	14.50	1.50	18.00
5/16-18 UNC	3.50	6.00	11.00	11.50	10.90	14.50	1.50	21.00
3/8-16 UNC	1.00	4.00	13.00	13.50	12.90	17.00	1.70	21.00
3/8-16 UNC	4.00	6.50	13.00	13.50	12.90	17.00	1.70	23.50